

DEEP LEARNING APPROACHES FOR RAILROAD INFRASTRUCTURE MONITORING: COMPARING VOLOGOVISION TRANSFORMERS

COMPARING YOLO & VISION TRANSFORMERS FOR DEFECT DETECTION

Advay Chandramouli, Hwapyeong Song, Mingyan Liu, Aayush Damai, Husnu S. Narman, Ph.D., and Ammar Alzarrad Ph.D.

2025 IEEE 16th Annual Ubiquitous Computing, Electronics & Mobile Communication Conference (UEMCON) *October 22-24, 2025*



- O1 Introduction
- O2 Machine Learning Models
- O₃ Methodology
- O4 Results
- 05 Conclusion
- **O6** Future Directions


Overview



Introduction


28.6+ million passengers rely on railroads for transportation, according to Amtrak passenger data from 2023 [1]

in 2022, due to rail defects exacerbating track geometry and structural integrity [2], [3]





Current Methods & Approaches



Early Machine Learning (ML)
applications
using decision trees, SVMs and logistic
regression models show promise in this
domain for feature extraction [7], [8]

Latest Deep Learning (DL)
advancements
in object detection have enabled realtime visual defect detection [9], [10]



Gap in Scholarly Literature




focusing on component-level detection for bolts, rails and fasteners [9], [10]

Vision Transformers (ViTs) show promise

in general object detection, but remain underexplored in railroad defect detection contexts [11], [12]

No studies directly benchmark

CNN-based object detectors and Transformer-based models in this domain



Research Question


How can deep learningbased object detection models be leveraged to detect defective railroad ties?



Machine Learning Models

Non-trivial selection, owing to the bevy of computer vision algorithms, resulting in the following study criterion:


- Supports real-time, multi-class detection tasks
- Effectively balances detection speed and localization accuracy
- Suitable for lightweight deployment environments





You Only Look Once (YOLO)


- Single-stage CNN detector
 - Partitions and processes whole image at once, enabling real-time detection
 [13]
- Outputs bounding boxes & confidence scores; object localization handled using Non-Maximum Suppression (NMS)
- YOLOv11 achieves higher mAP than
 YOLOv8 despite 22% fewer parameters
 [14]





Real-Time Detection Transformer (RT-DETR)

- Transformer architecture adapted for vision tasks, featuring hybrid encoder/decoder pipeline
 - Minimal NMS and learned object queries enables real-time detection
 [15]
- Captures both global context & finegrained features, adapts well with limited or imbalanced data [12]



Note: Convolutional backbone (e.g., ResNet) responsible for feature map extraction before transformer processing.



YOLOv11 Model Comparison

Model	Params (M)	Speed - CPU (ms)	Speed - T4 GPU (ms)
YOLO11n	2.6	56.1	1.5
YOLO11s	9.4	90	2.5
YOLO11m	20.1	183.2	4.7
YOLO11l	25.3	238.6	6.2
YOLO11x	56.9	462.8	11.3



RT-DETR Model Comparison

Version	Params (M)	Speed - T4 GPU (ms)
RT-DETR-L	32.9	8.8
RT-DETR-X	~67	13.5

Note: Parameter counts for RT-DETR vary with the chosen backbone (e.g., ResNet-50 vs ResNet-101). Values shown here are representative benchmarks.

- Notable trade-offs between model size, speed, and accuracy:
 - Larger models deliver higher accuracy but run slower, even with GPU acceleration
 - Smaller models achieve faster
 inference but at the cost of accuracy
- Both YOLOv11-L and RT-DETR-L provide comparable parameter counts and satisfy this study's selection criteria



Methodology

Dataset Overview:

- Collected overhead railroad footage using a custom-built camera rig
 - Extracted 573 frames from 5 minute contiguous video streams
- Sampled every 15th frame to ensure variance and a distinct set of ties per image



Dataset


Preprocessing & Annotation

Training & Evaluation Protocol




Data Preprocessing & Annotation

- Filtered dataset to <u>500 images</u> by removing blurred, over/underexposed, or obstructed frames
 - Padded to square dimensions while maintaining original 4:3 aspect ratio
- Annotated each image for following labels, using nested bounding boxes retained spatial context between ties and defects
 - Wood Ties
 - Wood Checks
 - Wood Decay
 - Missing Ties





Sample Annotations







Data Augmentation

- Applied following image transformations to augment dataset:
 - Contrast Stretching
 - Horizontal Flips
 - ±10° hue,
 - ±10% saturation,
 - ±5% brightness
 - Salt-and-pepper noise (0.1% pixels)

Class Label	Class Distribution
Wood Check	716
Wood Decay	1,329
Wood Ties	1,779



Training & Evaluation Protocol

I. Model Training

- Training & Validation: Fixed hyperparameter configuration with 5-fold cross-validation with 80/20 train-test split
- Hardware: NVIDIA A100 GPUs (40 GB memory, 432 tensor cores)



II. Evaluation Metrics

- F1 Score
- Precision
- Recall
- Mean Average Precision
 - IoU: 0.5 and 0.5-0.95

Results

Post-Training & Validation Evaluations:

- Plotted box loss, classification (CLS) loss, distribution focal loss over epoches for both models
 - Indicative of strong convergence, minimal overfitting and effective generalization to unseen data




Figure A: Loss graphs from best performing YOLOv11 Fold




Figure B: Loss graphs from best performing RT-DETR Fold



Quantitative Evaluation

Metric	YOLOv11-Large	RT-DETR-Large	Winner
F1 Score	0.9400 ± 0.0089	0.9300 ± 0.0114	YOLOv11
Precision	0.9696 ± 0.0077	0.9498 ± 0.0088	YOLOv11
Recall	0.9104 ± 0.0147	0.9119 ± 0.0152	RT-DETR
mAP50	0.9530 ± 0.0106	0.9321 ± 0.0094	YOLOv11
mAP50-95	0.9014 ± 0.0134	0.7898 ± 0.0131	YOLOv11



Error Analysis




Figure C: Normalized confusion matrix for bestperforming YOLOv11 fold; more balanced false positives, fewer extreme misclassifications




Figure D: Normalized confusion matrix for bestperforming RT-DETR fold; higher recall with inflated instances of misclassifying background as defects



Per-Class Performance

- Per-class detection accuracy averaged across 5 folds:
 - Both models achieve strong performance on Wood Ties (~99%)
 - RT-DETR performs slightly better on *Checks*; YOLOv11 outperforms on *Decay*

Class Label	YOLOv11	RT-DETR
Wood Check	0.90	0.92
Wood Decay	0.85	0.876
Wood Ties	0.99	0.992



Model Demonstration





Conclusions

- Object detection models effectively capture discrete defects and spatial relationships between tie conditions
- High-quality, consistent data paramount to maximizing DL's predictive power
- While transformer models (e.g., RT-DETR) show promise, CNNbased detectors (YOLOv11) remain superior for real-time speed, accuracy, and deployment



Limitations & Future Directions

- Address dataset constraints: field test footage captured on abandoned rail segments in West Virginia, limiting environmental variability (lighting, weather, defect types)
- Explore segmentation-based two-stage pipelines for finer localization
- Develop a defect severity rating system with governing bodies to translate model outputs into actionable maintenance insights



References

- [1] Amtrak, "Amtrak Fiscal Year 2023 ridership exceeds expectations as demand for passenger rail soars," Nov. 2023. [Online]. Available: https://media.amtrak.com/2023/11/amtrak-fiscal-year-2023-ridership-exceeds-expectations-as-demand-for-passenger-rail-soars/
- [2] U.S. Department of Transportation, "Rail data dashboard," 2023. [Online]. Available: https://data.transportation.gov/stories/s/v2un-y5se
- [3] National League of Cities, "Interactive rail safety map: See derailments in communities across the U.S.," 2023. [Online]. Available: https://www.nlc.org/resource/interactive-rail-safety-map-see-derailments-in-communities-across-the-u-s/
- [4] Y. Wang, Y. Wang, P. Wang, K. Ji, J. Wang, J. Yang, and Y. Shu, "Rail magnetic flux leakage detection and data analysis based on double-track flaw detection vehicle," Processes, vol. 11, p. 1024, 03 2023.
- [5] W. Gong, M. F. Akbar, G. N. Jawad, M. F. P. Mohamed, and M. N. A. Wahab, "Nondestructive testing technologies for rail inspection: A review," Coatings, vol. 12, p. 1790, 11 2022.
- [6] Y. Xia, S. W. Han, and H. J. Kwon, "Image generation and recognition for railway surface defect detection," Sensors, vol. 23, pp. 4793-4793, 05 2023.
- [7] S. M. Mirzaei, A. Radmehr, C. Holton, and M. Ahmadian, "In-motion, non-contact detection of ties and ballasts on railroad tracks," Applied Sciences, vol. 14, pp. 8804–8804, 09 2024. [Online]. Available: https://www.mdpi.com/2076-3417/14/19/8804
- [8] J. Sresakoolchai and S. Kaewunruen, "Railway defect detection based on track geometry using supervised and unsupervised machine learning," Structural Health Monitoring, vol. 21, p. 147592172110444, 01 2022.
- [9] A. Damai, H. Song, H. S. Narman, A. Lambert, and A. Alzarrad, "Enhancing railway safety: A machine learning approach for automated detection of missing track bolts," in Proc. ASCE Int. Conf. Computing in Civil Engineering (i3CE), New Orleans, LA, May 11–14 2025.
- [10] A. D'Arms, H. Song, H. S. Narman, N. C. Yurtcu, P. Zhu, and A. Alzarrad, "Automated railway crack detection using machine learning: Analysis of deep learning approaches," in Proc. 2024 IEEE 15th Annu. Inf. Technol., Electron. and Mobile Commun. Conf. (IEMCON), Berkeley, CA, Oct. 24–26 2024.
- [11] Y. Zhao, Z. Liu, D. Yi, X. Yu, X. Sha, L. Li, H. Sun, Z. Zhan, and W. J. Li, "A review on rail defect detection systems based on wireless sensors," Sensors, vol. 22, p. 6409, 01 2022. [Online]. Available: https://www.mdpi.com/1424-8220/22/17/6409
- [12] A. Phaphuangwittayakul, N. Harnpornchai, F. Ying, and J. Zhang, "Railtrack-davit: A vision transformer-based approach for automated railway track defect detection," Journal of Imaging, vol. 10, pp. 192–192, 08 2024.
- [13] J. Redmon, S. Divvala, R. Girshick, and A. Farhadi, "You Only Look Once: Unified, real-time object detection," arXiv preprint arXiv:1506.02640, 2015. [Online]. Available: https://doi.org/10.48550/arXiv.1506.02640
- [14] M. L. Ali and Z. Zhang, "The YOLO framework: A comprehensive review of evolution, applications, and benchmarks in object detection," Computers, vol. 13, no. 12, 2024. [Online]. Available: https://www.mdpi.com/2073-431X/13/12/336
- [15] Y. Zhao, W. Lv, S. Xu, J. Wei, G. Wang, Q. Dang, Y. Liu, and J. Chen, "Detrs beat yolos on real-time object detection," 2024. [Online]. Available: https://arxiv.org/abs/2304.08069
- [16] W. He, Y. Zhang, T. Xu, Y. Liang, and T. An, "Object Detection for Medical Image Analysis: Insights from the RT-DETR Model," arXiv preprint arXiv:2501.16469, Jan. 2025.



Thank You

To the <u>National Science Foundation</u>'s Research Experiences for Undergraduates (REU) Program, <u>Marshall University</u>, and the <u>U.S. Army Engineer Research & Development Center (ERDC)</u> for supporting this work.



QCJAS